




AUOW068

SPECIFICATION

HOUSING :CORROSION RESISTANT DIE CAST ALUMINIUM
 :WEATHERPROOF RUBBER GASKET
 :STAINLESS STEEL SCREWS
 SURFACE TREATMENT :ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV
 RESISTANT POLYESTER POWDER COAT
 DIFFUSER :OPAL ACRYLIC

FRAME :CAST ALUMINIUM
 COLOR :BLACK, WHITE, SILVER
 PROTECTION CLASS :PROTECTION CLASS EQUIVALENT TO IP 55
 INSTALLATION :WALL MOUNT
 APPLICATION :BUILDING, HOTEL, RESTAURANT, RESIDENTIAL
 PARKS, WALK WAYS, ETC.



MODEL	DIMENSION(mm.)		LAMP	LUMEN	LAMP TYPE
	L	W	HOLDER	[MAX]	
AUOW068	280	85	E 27	1170 lm.	PL 11, 14, 18W.
			G 23 x 2	600 lm.	2 x PLS 7, 9W.
			G 24	1800 lm.	PLC 13, 18, 26W.

WIRES

<input type="checkbox"/> THW	<input type="checkbox"/> 70 °C	<input type="checkbox"/> 0.5 SQmm.	<input type="checkbox"/> 13 AWG
<input type="checkbox"/> UL STYLE & CSA TYPE	<input type="checkbox"/> 90 °C	<input type="checkbox"/> 1.0 SQmm.	<input type="checkbox"/> 15 AWG
<input type="checkbox"/> HEATER WIRE	<input type="checkbox"/> 105 °C	<input type="checkbox"/> 1.5 SQmm.	<input type="checkbox"/> 17 AWG
<input type="checkbox"/> OTHER	<input type="checkbox"/> 200 °C	<input type="checkbox"/> 2.5 SQmm.	<input type="checkbox"/> 20 AWG