



AU-DL09

SPECIFICATION

HOUSING :HIGH COLD-ROLLED STEEL SHEET FORMED BY
HIGH QUALITY MACHINES

SURFACE TREATMENT :ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV
RESISTANT POLYESTER POWDER COAT


REFLECTOR :HIGH GRADE ANODIZED ALUMINIUM (DIAMOND)

COLOR :WHITE, BLACK

PROTECTION CLASS :PROTECTION CLASS EQUIVALENT TO IP 20

INSTALLATION :SURFACE MOUNT

APPLICATION :OFFICE BUILDING, HOSPITAL, DEPARTMENT STORE
HOTEL, RESTAURANT, GOVERNMENTAL BUILDING
SHOP, RESIDENTIAL, ETC.



MODEL	DIMENSION(mm.)			LAMP HOLDER	LUMEN (MAX)	LAMP TYPE
	∅	W	H			
AU-DL09-14	140	140	170	E 27	1000 lm.	PL14, 18, 23W.
AU-DL09-17	170	170	230	E 27	1500 lm.	PL14, 18, 23W.

WIRES

<input type="checkbox"/> THW	<input type="checkbox"/> 70°C	<input type="checkbox"/> 0.5 SQmm.	<input type="checkbox"/> 13 AWG
<input type="checkbox"/> UL STYLE & CSA TYPE	<input type="checkbox"/> 90°C	<input type="checkbox"/> 1.0 SQmm.	<input type="checkbox"/> 15 AWG
<input type="checkbox"/> HEATER WIRE	<input type="checkbox"/> 105°C	<input type="checkbox"/> 1.5 SQmm.	<input type="checkbox"/> 17 AWG
<input type="checkbox"/> OTHER	<input type="checkbox"/> 200°C	<input type="checkbox"/> 2.5 SQmm.	<input type="checkbox"/> 20 AWG