




**AU-D4N/2**

**SPECIFICATION**

HOUSING	:HIGH COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES	COLOR	:WHITE, SILVER
SURFACE TREATMENT	:ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT POLYESTER POWDER COAT	PROTECTION CLASS	:PROTECTION CLASS EQUIVALENT TO IP 20
REFLECTOR	:HIGH GRADE ANODIZED ALUMINIUM (POLISHED)	INSTALLATION	:RECESS CONCEAL CEILING
FRAME	:STEEL WITH POLYESTER POWDER COAT	APPLICATION	:BUILDING, HOSPITAL, DEPARTMENT STORE, HOTEL CONDOMINIUM, RESTAURANT, SHOWROOM, SHOP, RESIDENTIAL, ETC.




MODEL	DIMENSION(mm.)		CUT OUT C (mm.)	LAMP	LUMED (MAX)	LAMP TYPE
	Ø	H		HOLDER		
AU-D4N/2	145	165	125	E 27	800 lm.	PL 8, 11, 14W.
				G 23	400 lm.	PLS 7W.
				G 24	900 lm.	PLC 13W.



**AU-D5N/2**

**SPECIFICATION**

HOUSING	:HIGH COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES	COLOR	:WHITE, SILVER
SURFACE TREATMENT	:ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT POLYESTER POWDER COAT	PROTECTION CLASS	:PROTECTION CLASS EQUIVALENT TO IP 20
REFLECTOR	:HIGH GRADE ANODIZED ALUMINIUM (POLISHED)	INSTALLATION	:RECESS CONCEAL CEILING
FRAME	:STEEL WITH POLYESTER POWDER COAT	APPLICATION	:BUILDING, HOSPITAL, DEPARTMENT STORE, HOTEL CONDOMINIUM, RESTAURANT, SHOWROOM, SHOP, RESIDENTIAL, ETC.




MODEL	DIMENSION(mm.)		CUT OUT C (mm.)	LAMP HOLDER	LUMED (MAX)	LAMP TYPE
	Ø	H				
AU-D5N/2	175	185	155	E 27	1550 lm.	PL 14, 18, 20, 23W.
					6200 lm.	MV 80, 125W.
					13500 lm.	MH 70, 100, 150W.
					5600 lm.	HPS 70W.
				G 23	600 lm.	PLS 9W.
				G 24	1800 lm.	PLC 13, 18, 26W.



**AU-D6N/2**

**SPECIFICATION**

HOUSING	:HIGH COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES	COLOR	:WHITE, SILVER
SURFACE TREATMENT	:ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT POLYESTER POWDER COAT	PROTECTION CLASS	:PROTECTION CLASS EQUIVALENT TO IP 20
REFLECTOR	:HIGH GRADE ANODIZED ALUMINIUM (POLISHED)	INSTALLATION	:RECESS CONCEAL CEILING
FRAME	:STEEL WITH POLYESTER POWDER COAT	APPLICATION	:BUILDING, HOSPITAL, DEPARTMENT STORE, HOTEL CONDOMINIUM, RESTAURANT, SHOWROOM, SHOP, RESIDENTIAL, ETC.



MODEL	DIMENSION(mm.)		CUT OUT C (mm.)	LAMP HOLDER	LUMED (MAX)	LAMP TYPE
	Ø	H				
AU-D6N/2	220	230	200	E 27	1550 lm.	PL 18, 20, 23W.
					9300 cd.	PAR 38, 120W.
					6200 lm.	MV 80, 125W.
					13500 lm.	MH 70, 100, 150W.
					5600 lm.	HPS 70W.
				G 24	1800 lm.	PLC 13, 18, 26W.