



AUF G1-120-140

SPECIFICATION

HOUSING :HIGH GRADE COLD-ROLLED STEEL SHEET FORMED
BY HIGH QUALITY MACHINES

SURFACE TREATMENT :ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV
RESISTANT WHITE POLYESTER POWDER COAT

REFLECTOR :WHITE STOVED ENAMELLED WIRE GUARD

WIRES :THW, TIS.11-1988 STANDARD

LAMP HOLDER W/P :SPRING LOCKED TYPE HIGH-HEAT RESISTANCE,
TIS344-1987 STANDARD


STARTER HOLDER :ROTOR LOCKED TYPE HIGH-HEAT RESISTANCE,
TIS344-1987 STANDARD

PROTECTION CLASS :PROTECTION CLASS EQUIVALENT TO IP 20

INSTALLATION :SURFACE MOUNT OR SUSPEND MOUNT

APPLICATION :FACTORY, WAREHOUSE, CARPARK, ETC.

COMPLETE SET* :INCLUDING BALLAST, LAMP, STARTER NORMAL
FOR T8 LAMP



MODEL	LAMP	DIMENSION(mm.)			WEIGHT (kg.)
		L	W	H	
AUF G1-120	1 x 18W. T8	635	67	118	2.40
AUF G1-140	1 x 36W. T8	1245	67	118	3.00

INSTALLATION : SURFACE MOUNT OR SUSPEND MOUNT