



AUF I1

SPECIFICATION

HOUSING :HIGH GRADE COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES

SURFACE TREATMENT :ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT WHITE POLYESTER POWDER COAT

WIRES :THW, TIS.11-1988 STANDARD

LAMP HOLDER :SPRING LOCKED DUSTPROOF TYPE HIGH-HEAT RESISTANCE, TIS344-1987 STANDARD FOR T8 LAMP
:ROTOR LOCKED DUSTPROOF TYPE HIGH-HEAT RESISTANCE, TIS344-1987 STANDARD FOR T5 LAMP


PROTECTION CLASS :PROTECTION CLASS EQUIVALENT TO IP 20

INSTALLATION :SURFACE MOUNT OR SUSPEND MOUNT

APPLICATION :FACTORY, SHOP, WAREHOUSE, CANTEEN, ETC.

COMPLETE SET* :INCLUDING BALLAST, LAMP, STARTER NORMAL FOR T8 LAMP

COMPLETE SET** :INCLUDING ELECTRONIC BALLAST, LAMP FOR T5 LAMP



MODEL	LAMP	DIMENSION(mm.)			WEIGHT (kg.)
		L	W	H	
AUF I1-220	2 x 18W. T8	635	240	105	3.40
AUF I1-240	2 x 36W. T8	1245	240	105	4.95
AUF I1-232	2 x 32W. T8	1245	240	105	4.95
AUF I1-320	3 x 18W. T8	635	345	115	5.15
AUF I1-340	3 x 36W. T8	1245	345	115	7.90

INSTALLATION : SURFACE MOUNT OR SUSPEND MOUNT