

AUF MCR

SPECIFICATION

HOUSING :HIGH GRADE COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES
:WEATHERPROOF RUBBER GASKET
:SILICONE GASKET

SURFACE TREATMENT :ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT WHITE POLYESTER POWDER COAT

REFLECTOR :PARABOLIC HIGH PURITY ANODIZED ALUMINIUM
99.85% MIRROR FINISH, TOTAL REFLECTION 87%
(DIN 5063-3) FORM GERMANY

(OPTIONAL) :PARABOLIC HIGH PURITY ANODIZED ALUMINIUM
99.99% MIRROR FINISH, TOTAL REFLECTION 95%
(DIN 5063-3) FORM GERMANY

DIFFUSER :OPAL ACRYLIC (OP), CLEARACRYLIC (CL), STIPPLE ACRYLIC (ST), PRISMATIC ACRYLIC (PR)

FRAME :WHITE ENAMEL STEEL

WIRES :THW, TIS.11-1988 STANDARD


LAMP HOLDER :ROTOR LOCKED TYPE HIGH-HEAT RESISTANCE, TIS344-1987 STANDARD

PROTECTION CLASS :PROTECTION CLASS EQUIVALENT TO IP 55

INSTALLATION :RECESS T-BAR CEILING, RECESS CONCEAL CEILING

APPLICATION :HOSPITAL, FACTORY, WAREHOUSE, CLEAN ROOM, ETC.

COMPLETE SET* :INCLUDING BALLAST, LAMP, STARTER NORMAL FOR T8 LAMP



MODEL	LAMP	DIMENSION(mm.)			CUT OUT(mm.)		WEIGHT (kg.)
		L	W	H	L	W	
AUF MCR-240A	2 x 36W. T8	1255	295	120	1230	280	7.50
AUF MCR-240B	2 x 36W. T8	1255	595	120	1230	580	10.30
AUF MCR-340	3 x 36W. T8	1255	595	120	1230	580	11.30
AUF MCR-440	4 x 36W. T8	1255	595	120	1230	580	11.30