



AUFTM2-240A

SPECIFICATION

HOUSING :HIGH GRADE COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES

SURFACE TREATMENT :ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT WHITE POLYESTER POWDER COAT

REFLECTOR :PARABOLIC HIGH PURITY ANODIZED ALUMINIUM
99.85% MIRROR FINISH, TOTAL REFLECTION 87%

(OPTIONAL) :PARABOLIC HIGH PURITY ANODIZED ALUMINIUM
99.99% MIRROR FINISH, TOTAL REFLECTION 95%

LOUVER :PARABOLIC HIGH PURITY ANODIZED ALUMINIUM
99.85% MIRROR FINISH FOR LONGITUDINAL & PROFILE ALUMINIUM CROSS BLADE

WIRES :THW, TIS.11-1988 STANDARD

LAMP HOLDER :ROTOR LOCKED TYPE HIGH-HEAT RESISTANCE, TIS344-1987 STANDARD


STARTER HOLDER :ROTOR LOCKED TYPE HIGH-HEAT RESISTANCE, TIS344-1987 STANDARD

PROTECTION CLASS :PROTECTION CLASS EQUIVALENT TO IP 20

INSTALLATION :RECESS T-BAR CEILING, RECESS CONCEAL CEILING (M-BAR)

APPLICATION :OFFICE BUILDING, HOSPITAL, DEPARTMENT STORE
UNIVERSITY, GOVERNMENTAL BUILDING, SHOP ETC.

COMPLETE SET* :INCLUDING BALLAST, LAMP, STARTER NORMAL FOR T8 LAMP



MODEL	LAMP	DIMENSION(mm.)			CUT OUT(mm.)		WEIGHT (kg.)
		L	W	H	L	W	
AUFTM2-240A	2 x 36W. T8	1195	295	80	1180	280	6.10

INSTALLATION : RECESS T-BAR CEILING, RECSS CONCEAL CEILING (M-BAR)