



**AUOT104**

**SPECIFICATION**

HOUSING	:CORROSION RESISTANT CAST ALUMINIUM	COLOR	:BLACK, WHITE, SILVER
	HOUSING WITH STEEL POLE	PROTECTION CLASS	:PROTECTION CLASS EQUIVALENT TO IP 55
SURFACE TREATMENT	:ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT POLYESTER POWDER COAT	INSTALLATION	:SURFACE FLOOR MOUNT
DIFFUSER	:VANDAL RESISTANT OPAL GLASS	APPLICATION	:CAR PARK, WALK WAYS, PARKS, ROAD WAYS ETC.
	:VANDAL RESISTANT CLEAR GLASS		



MODEL	DIMENSION(mm.)		LAMP HOLDER	LUMEN (MAX)	LAMP TYPE
	W	H			
AUOT104-10 (10")	250	2250	E 27	1550 lm.	PL 18,23W.
AUOT104-12 (12")	300	3000	E 27	1550 lm.	PL 23W.
AUOT104-14 (14")	350	4000	E 27	1550 lm.	PL 23W.
				3700 lm.	MV 80W.
				5600 lm.	HPS 70W.
				5300 lm.	MH 70W.
AUOT104-16 (16")	400	5000	E 40	12700 lm.	MV 250W.
				25000 lm.	HPS 250W.
				18000 lm.	MH 250W.